



The Best Ideas are the Ones that Stick!

AFTC SilverTape® Industrial Product Line

Type of AFT	Thick (mils)	Color	Part #
Direct Foam or Self Stick	16	grey	5004
	16	white	5005
100% acrylic core with no coating, Direct Foam are designed to bond to bare metals, glass and most clear plastics. Offered in grey and white. When bonded properly, the Direct Foam family of SilverTapes will provide users with a strong and unbreakable bond.	25	grey	5046
	25	white	5330
	31	grey	5008
	31	white	5032
	47	grey	5011
	47	white	5350
	47	white	5013
	63	grey	5056
	79	white	5312
	91	grey	5091
118	white	5359	
Standard width 900mm (35.4") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
LSE (Firm Core)	16	black	6404
Firm / dense acrylic core with a high performance Low Surface Energy acrylic PSA coating on both sides. Ideal for ceramics, silicones, powder coated materials and other LSE surfaces.	25	black	6406
	31	black	6408
	47	black	6411
	63	black	6415
	79	black	6420
	91	black	6423
Standard width 900mm (35.4") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
LSE (Soft Core)	16	black	6604
Offers the same LSE acrylic PSA coating as the 64 series, but the 66 series utilizes a softer less dense core for better conformability.	25	black	6606
	31	black	6608
	47	black	6611
	63	black	6615
Standard width 900mm (35.4") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
New LSE (Med density)	16	white/black/grey	6804
Medium density acrylic core with a "new" high perf. Low Surface Energy PSA coating on both sides. Bonds to paints, coatings, PP and PE.	25	white/black/grey	6806
	31	white/black/grey	6808
	47	white/black/grey	6811
	63	white/black/grey	6815
Standard width 900mm (35.4") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
Structural Glazing	91	grey	SGG
Used on structural glazing applications, facades and eliminates need for silicones or liquid sealing systems	91	black	SGB
	91	white	SGW
Standard width 900mm (35.4") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
Coated Direct Foam	16	grey	5326
100% foamed acrylic core with a very stable general purpose acrylic PSA coating on both sides. The Coated Direct Foam line is offered in grey, white and black in wide range of thicknesses from 8 mils to 120 mils. This is AFTC USA's most versatile and popular family of SilverTape® products. This line is designed to bond to wide range of substrates. Provides unbreakable shear and tensile with good peel.	25	black	5319
	25	grey	5332
	25	grey	5336
	25	white	5333
	31	white	5335
	31	grey	5339
	47	black	5347
	47	grey	5352
	47	grey	5341
	47	white	5345
	63	black	5357
	63	white	5355
	63	grey	5356
	79	grey	5390
	91	grey	5391
	91	black	5392
	118	white	5399
Standard width 900mm (35.4") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
Clear (Direct Foam)	10	clear	8502
Ultra clear foamed acrylic core that offers unmatched optical clarity. Offered in thicknesses of 10 mils up to 120 mils. This is the perfect product line for POP, Signage, LED's, displays, shower doors, windows or where clarity is important.	16	clear	5304
	20	clear	5305
	31	clear	5308
	39	clear	5310
	59	clear	5315
	79	clear	5320
	98	clear	5325
	118	clear	5321
Standard width 500mm (19.7") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
Clear Remove	25	clear	5106
Clear acrylic core with the added feature of being removable on many surfaces.	30	clear	5108
	60	clear	5115
Standard width 500mm (19.7") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
Low Temp	30	grey	5337
Aggressive high performance PSA coating with a firm acrylic core designed to be able to bond down to 30 °F.	47	grey	5343
	47	white	5351
	60	grey	5353
Standard width 900mm (35.4") X 18 and 36 yds			



Type of AFT	Thick (mils)	Color	Part #
Structural Cladding	25	grey	SC06B
<i>Used to mount or bond metal frames, aluminium composite panels in wall systems replacing mechanical fasteners and liquid sealing systems.</i>	25	black	SC06G
	25	white	SC06W
	45	grey	SC11B
	45	black	SC11G
	45	white	SC11W
	60	grey	SC15B
	60	black	SC15G
	60	white	SC15W
Standard width 900mm (35.4") X 18 and 36 yds			

Type of AFT	Thick (mils)	Color	Part #
High Temp/ Direct	16	grey	6004
<i>High Temp Pre-Powder Coating, will withstand the powder coating process.</i>	30	grey	6008
	45	grey	6011
Standard width 900mm (35.4") X 18 and 36 yds			

Note: The information provided herein and all data enclosed should be considered representative. This information shall not be used for specification purposes. It is the sole responsibility of the user to evaluate, and make the final determination if the AFTC product(s) is suitable for its intended purpose.

Available sizes:
<i>Jumbo: 900mm x 330 meters (core 3")</i>
<i>Log: 900mm x 33/66 meters (core 3")</i>
<i>Slit: 5 – 250mm x 5 meters - 132 meters (core 3")</i>
<i>Spools: 5 – 25mm x max 900 meters (core 6")</i>

Application Guidelines:
<i>Identify your substrate or surface</i> <i>Use a micro fiber or lint free towel</i> <i>Lightly wipe away loose dirt</i> <i>Apply a 50 / 50 mix of IPA and H²O</i> <i>Make sure surface is dry after cleaning</i> <i>Firm pressure must be used</i> <i>Allow a min of 24 hrs for tape to wet out</i>

Type of AFT	Thick (mils)	Color	Part #	
Ultra Thin	6	black	815	
<i>The AFTC Ultra Thin line offers a strict consistency in thickness with outstanding shear and tensile strength for applications where the profile of the application is critical.</i>	6	white	816	
	8	black	820	
	8	white	821	
	9	grey	8302	
	9	white	8303	
	16	grey	8304	
	9	black	8402	
	9	white	8403	
	16	black	8404	
	10	clear	8502	
	16	clear	8504	
	Standard width 900mm (35.4") X 36 yds & 60 yds			

Type of AFT	Thick (mils)	Color	Part #	
Heat activated	31	grey	HA7308	
<i>Designed with AFTC's proprietary Heat Activated hot melt adhesive developed specifically to bond to EPDM sponge rubber (Sanoprene[®]) when exposed to heat. On the other side is AFTC SilverTape AFT's. AFTC offers several standard Heat Activated products to meet all of your needs.</i>	47	grey	HA7312	
	16	grey	HA7404	
	31	grey	HA7408	
	47	grey	HA7412	
	16	black	HA7604	
	31	black	HA7608	
	47	black	HA7612	
	47	black	HA7912	
	47	blk or gr	HA8012 L61	
	Standard width: Sold in spools from 5mm - 25mm			

Type of AFT	Thick (mils)	Color	Part #
Sealing Tape	40	Transparent	2510
<i>Extremely aggressive single sided transparent acrylic foam w/ durable ionomer film</i>	80	Transparent	2580
Standard width: Sold only in slit roll format			

|

|

|